

HELUKABEL®


Ktl. Nr. 15071128

Normen / Norms


DIN EN 60529 :1991/A2:2013/AC:2019-02

DIN EN IEC 63000:2018


DIN EN 62471:2009




Netzanschluss / Main Supply	12-30 VDC
Leistung / Power	38,6 W
Dimmbar / Dimmable	0-10V
Anschluss / Connection Type	M12, 5-Pol, A-Cod.
Durchschleifbar / Loophthrough	Nein / No
Pinbelegung / Pin assignment	



Bestückt / Fitted With	LED
Lichtfarbe / Light Colour	5700 K
Lichstrom(Brutto) / Lum. Flux(Gross)	5888 lm
Lichstrom(Netto) / Lum. Flux(Net)	4126 lm
Effizienz(Brutto) / Efficiency(Gross)	153 lm/W
Effizienz(Netto) / Efficiency(Net)	107 lm/W
Abstrahlwinkel / Beam Angle	100°
Farbtreue / Colour Rendering	RA / CRI >80
Photobiological Safety	RG-1



Gehäuse / Housing	Aluminium
Abdeckung / Cover	ESG, Diff.
Drehbar / Rotatable	Ja / Yes
Gewicht(Netto) / Weight(Net)	0,99 kg
Betriebstemperatur / Operating Temp.	-20°C / +50°C
Lebensdauer / Lifetime	min. 60000 h
Befestigung / Fastening	2x Endhalter / 2x Brackets



a= 745mm b= 765mm

HELU Connectivity Solutions Bielefeld GmbH • Bechterdisser Straße 67 • D-33719 Bielefeld

rev.07.04.2025